










Modules					 Une infinité de design possible				
Références		2ES-7-36 (P ou M)	2ES-10-36 (P ou M)	2ES-15-36 (P ou M)	2ES-18-52 (P ou M)	2ES-7-56 (P ou M)	2ES-38-36 (P ou M)	2ES-38-48 (P ou M)	2ES-38-60 (P ou M)
Puissance (Wc) à l'année de fabrication		155 (P)	150 (P)	145 (P)	214 (P)	270 (M)	152 (P)	202 (P)	253 (P)
Puissance (Wc) en 2020		180 (M)	180 (M)	180 (M)	260 (M)	280 (M)	180 (M)	240 (M)	300 (M)
Transparence		17%	18%	19%	29%	15%	42%	38%	37%
Côte de verre	x (mm)	1069	1084	1081	1316	1234	1216	1216	1216
	y (mm)	1036	1050	1070	1430	1357	1336	1637	2000
Albédiu: X (mm) 		1095	1117	1115	1350 (ci)	1268 (ci)	1250 (ci)	1250 (ci)	1250 (ci)
Albétra: Y (mm) 		1051	1064	1085	1444	1371	1350 (ci)	1651 (ci)	2014 (ci)
Boite de jonction 		V6 	V6 	V6 	V8 	V8 	V6 	V8 	V10 

Ce document est la propriété de 2ES.  
Toutes reproduction ou transmission sans accord est interdite.

Brevet n°1: PA2589FR-0800217  
Brevet n°2: PA2759FR-0806382  
Brevet n°3: PA2775FR-0807523

(P): cellules en polycristallin  
(M) cellules en monocristallin  
(ci): côte imposée